

CLAIMS

What is claimed is:

- 5 1. A sensor for detecting a fluid level in a container, the sensor comprising first and second electrodes arranged such that a majority of their areas are vertically and horizontally offset from each other.
- 10 2. The sensor of claim 1, wherein the first and second electrodes are arranged such that their areas are substantially vertically and horizontally offset from each other.
- 15 3. The sensor of claim 1, wherein the first and second electrodes are arranged such that their areas are completely vertically and horizontally offset from each other.
- 20 4. The sensor of claim 1, wherein the first and second electrodes are vertically spaced from each other.
- 25 5. The sensor of claim 1, wherein the electrodes comprise substantially two-dimensional plates.
6. The sensor of claim 1, further comprising a conductor coupled to each of the first and second electrodes.
7. The sensor of claim 6, wherein the conductors coupled to each of the first and second electrodes are also coupled to control circuitry.

8. The sensor of claim 7, wherein conductors coupled to each of the first and second electrodes are coupled to the control circuitry through a Zero Insertion Force connector.

34073

4099167

Figure 1 10, 40, 50

4099167

Figure 1

10, 40, 50

4099167

Figure 1

10, 40, 50

4099167

50

4099167

50, 10

Find

Find

Sub
a1

-14-

a'
conced

9. The sensor of claim 1, further comprising control circuitry, the control circuitry configured to supply an oscillating signal to one of the first and second electrodes having a frequency greater than 1 MHZ.

5 10. The sensor of claim 9, wherein the control circuitry is configured to supply a signal at a frequency of at least about 4 MHZ.

11. The sensor of claim 10, wherein the control circuitry is configured to supply a signal at a frequency of at least about 8 MHZ.

10

12. The sensor of claim 1, further comprising control circuitry configured to detect a change in a capacitance of the sensor. 5135485 abstract

Sub B1 Ant

13. The sensor of claim 1, further comprising at least one alarm responsive to an output signal of the sensor. 5135485 figure.

15

14. The sensor of claim 1, wherein the electrodes are horizontally spaced. 4099167 figure

15. The sensor of claim 1, wherein the first and second electrodes are isolated from a volume within the container. 4099167 figure

20

16. The sensor of claim 15, wherein the first and second electrodes are placed on a wall of the container. 4099167 figure

25

17. The sensor of claim 16, further comprising a mounting structure to which the first and second electrodes are affixed. 4099167 (40) 5135484(11)

18. The sensor of claim 17, wherein the mounting structure is a thin electrically insulative film.

30

19. The sensor of claim 18, wherein the thin electrically insulative film is Mylar.

Sub B1 Ant

20. The sensor of claim 15, wherein the electrodes are placed within the wall of the container.

Sub a3

21. A method for detecting a level of a fluid within a container, comprising:

5 placing a capacitive structure including first and second electrodes arranged such that a majority of their areas are vertically and horizontally offset from each other on a wall of the container;

driving the capacitive structure at a frequency of more than about 1 MHz and

generating an output signal from the capacitive structure responsive thereto;

10 adjusting a fluid level within the container; and

detecting a change in the output signal responsive to the adjusting of the fluid level.

Sub B1 Ant

22. The method of claim 21, wherein placing a capacitive structure on a wall of the container comprises placing a capacitive structure within the wall of the container.

15

23. The method of claim 21, wherein driving the capacitive structure at a frequency of more than about 1 MHz further comprises driving the capacitive structure at a frequency of at least about 4 MHz.

20

Sub a4

24. The method of claim 21, wherein driving the capacitive structure at a frequency of more than about 1 MHz further comprises driving the capacitive structure at frequency of at least about 8 MHz.

Sub B1 Ant

25. The method of claim 21, wherein placing the capacitive structure on a wall of the container comprises forming the capacitive structure on a mounting structure and affixing the mounting structure to an exterior wall of the container with adhesive.

25

30

26. The method of claim 21, wherein placing the capacitive structure on a wall of the container comprises forming the capacitive structure on the wall.

27. The sensor of claim 21, further comprising determining whether the output signal exceeds a reference signal.

28. The method of claim 27, further comprising initiating at least one alarm if the output signal exceeds a reference signal.

29. The method of claim 28, wherein the at least one alarm is at least one of an audible alarm and a visual alarm.